# Fire Resistant BOP Control Line Hose 3000 PSI

Flame-resistant hydraulic BOP control line rated 3,000 PSI working, 12,000 PSI burst

**Application:**
Hydraulic control line for blowout preventers (BOP), and for any hydraulic service where flame resistance is required.

**Tube:**
Black oil resistant NBR

**Reinforcement:**
Two high tensile steel wires braided

**Cover:**
Thick red synthetic high temperature and flame resistant rubber

**Size range:**
**3/8" – 1" (10 mm – 25 mm)**

**Working pressure:**
**3,000 PSI**

**Temperature:**
**-40°F/+250°F (-40°C/+121°C)**

**Best for:**
**Hydraulic blowout-preventer control lines and other service where flame resistance is required**

**Marking:**
PARAGON




| PART NUMBER | ID | | OD | | WORKING PRESSURE | | BURST PRESSURE | | BEND RADIUS | | WEIGHT | | COIL LENGTH | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | in | mm | in | mm | PSI | bar | PSI | bar | in | mm | lb/ft | kg/m | ft | m |
| **FBOP-06-3000** | 3/8" | 10 | 1 | 25 | 3000 | 207 | 12000 | 827 | 2.56 | 65 | 0.54 | 0.8 | 200 | 61 |
| **FBOP-08-3000** | ½" | 13 | 1.12 | 28 | 3000 | 207 | 12000 | 827 | 3.54 | 90 | 0.74 | 1.1 | 200 | 61 |
| **FBOP-12-3000** | ¾" | 19 | 1.37 | 35 | 3000 | 207 | 12000 | 827 | 4.72 | 120 | 1.22 | 1.82 | 200 | 61 |
| **FBOP-16-3000** | 1" | 25 | 1.66 | 42 | 3000 | 207 | 12000 | 827 | 5.9 | 150 | 1.67 | 2.49 | 200 | 61 |

Safety factor 4:1 (burst to working pressure).