Premium PVC/Nitrile Discharge Hose

Seven sizes from 1½″ to 8″, rated 300 PSI at 1½″ down to 150 PSI from 4″ up, at 60 °F. −20 °F to +176 °F, in 200 ft (61 m) rolls.

Application:
Layflat discharge hose for agriculture, construction, industrial wash-down, mining and dewatering, irrigation, water-pump discharge and cable covering, with limited oil and chemical service.

Tube:
Black PVC/Nitrile (tube and cover extruded in one stage)

Reinforcement:
High-tensile polyester yarn

Cover:
Black PVC/Nitrile (tube and cover extruded in one stage)

Size range:
1½" – 8" (38 mm – 203 mm)

Working pressure:
150–300 PSI by size (rated at 60°F)

Temperature:
−20°F to +176°F (−29°C to +80°C)

Best for:
Water-pump discharge, mining and dewatering, irrigation, agriculture, construction, industrial wash-down, cable covering, limited oil and chemical service

Marking:
PARAGON



PART NUMBER	ID		WORKING PRESSURE		WALL		WEIGHT		COIL LENGTH	
	in	mm	PSI	bar	in	mm	lb/ft	kg/m	ft	m
BKFW-150-300-200	1½"	38	300	21	0.07	1.8	0.2	0.3	200	61
BKFW-200-220-200	2"	51	220	15	0.07	1.8	0.27	0.4	200	61
BKFW-250-200-200	2½"	64	200	14	0.09	2.3	0.38	0.57	200	61
BKFW-300-175-200	3"	76	175	12	0.09	2.3	0.48	0.71	200	61
BKFW-400-150-200	4"	102	150	10	0.09	2.3	0.71	1.06	200	61
BKFW-600-150-200	6"	152	150	10	0.12	3	1.08	1.61	200	61
BKFW-800-150-200	8"	203	150	10	0.13	3.3	1.85	2.75	200	61

Longer lengths available on request.