



PVC/Nitrile Discharge Hose

Eight sizes from 1½" to 10", rated 300 PSI at 1½" down to 150 PSI from 4" up, at 60 °F. -20 °F to +176 °F, in 200 ft (61 m) rolls.

Application:

Agriculture, construction, industrial wash-down, mining and dewatering, irrigation, water pump discharge, cable covering, limited oil and chemical. Longer lengths available on request.

Tube:

Black PVC/Nitrile (tube and cover extruded in one stage)

Reinforcement:

High-tensile polyester yarn

Cover:

Black PVC/Nitrile (tube and cover extruded in one stage)

Working pressure:

150–300 PSI by size (rated at 60°F)

Temperature:

-20°F to +176°F (-29°C to +80°C)

Marking:



PART NO.	ID		Wall		W.P.	Weight		Max. L
	Inch	mm	Inch	mm	PSI	lbs/ft	Kg/m	ft/m
BKFW-150-300-200	1½"	38	0.07	1.8	300	0.2	0.3	200/61
BKFW-200-220-200	2"	51	0.07	1.8	220	0.27	0.4	200/61
BKFW-250-200-200	2½"	64	0.09	2.3	200	0.38	0.57	200/61
BKFW-300-175-200	3"	76	0.09	2.3	175	0.48	0.71	200/61
BKFW-400-150-200	4"	102	0.09	2.3	150	0.71	1.06	200/61
BKFW-600-150-200	6"	152	0.12	3.0	150	1.08	1.61	200/61
BKFW-800-150-200	8"	203	0.13	3.3	150	1.85	2.75	200/61
BKFW-1000-150-200	10"	254	0.15	3.8	150	2.86	4.26	200/61