HIGH TEMPERATURE HOSE

SEA100 R5-J1402 DOT All FM VSS 106

Application:
Medium pressure hydraulic lines, fuel oil, antifreeze solution, air and water.

Tube:
Oil resistant synthetic rubber.

Reinforcement:
One high tensile steel braid.

Cover:
Black braided high tensile textile cord.

Temperature:
-40°F/+212°F (-40°C /+100°C)

Air max T:
+160°F(+70°C)

Safety factor:
1:4

Marking:
PARAGON



PART NO.	ID		OD		pressure		Min. b. r.	Weight		Max. L
	Inch	mm	Inch	mm	W.P. PSI	B.P. PSI	Inch	lbs./ft	Kg/m	ft/m
BKR5-03	3/16	5	0.52	13.20	3000	12000	2.99	0.16	0.230	200/61
BKR5-04	1/4	6.3	0.58	14.80	3000	12000	3.39	0.19	0.270	200/61
BKR5-05	5/16	8	0.68	17.30	2250	9000	4.02	0.24	0.350	200/61
BKR5-07	13/32	10.3	0.77	19.50	2000	8000	4.61	0.28	0.404	200/61
BKR5-10	1/2	12.5	0.92	23.40	1750	7000	5.51	0.38	0.560	200/61
BKR5-12	5/8	16	1.08	27.40	1500	6000	6.50	0.46	0.670	200/61
BKR5-16	7/8	22	1.24	31.40	800	3200	7.36	0.47	0.690	200/61
BKR5-20	1 1/8	29	1.50	38.10	625	2500	9.02	0.58	0.850	200/61
BKR5-24	1 3/8	35	1.75	44.50	525	2000	10.51	0.72	1.060	200/61
BKR5-32	1 13/16	46	2.22	56.40	350	1400	13.27	0.91	1.350	200/61