



PETROLEUM HOSE

Tank Truck Suction & Discharge Hose

Application:

Oil suction and discharge hose suitable for petroleum products.

Tube:

Black smooth synthetic rubber, resistant to mineral oils and fuels with maximum 50% aromatic content.

Reinforcement:

High tensile textile plies and helix wire embedded and antistatic wire.

Cover:

Black, smooth conductive rubber, abrasion, oil, fuel, ozone and weather resistant. Flame resistant according TRbF – 131 – Teil 2 - § 5.5.

Working Pressure:

150 PSI, 10 bar

Nominal Burst Pressure:

450 PSI, 30 bar

Temperature:

-22°F/+194°F (-30°C /+90°C)

Marking:

 PARAGON



PART NO.	ID		OD		Vacuum	Min. b. r.	Weight		Max. L
	Inch	mm	Inch	mm	In. hg	Inch	Lbs./ft	Kg/m	ft /m
TTSH-075-150	3/4	19.0	1.18	30	24	4.5	0.37	0.55	200/61
TTSH-100-150	1	25	1.41	36	24	5.9	0.46	0.68	200/61
TTSH-125-150	1¼	32	1.69	43	24	7.5	0.63	0.94	200/61
TTSH-150-150	1½	38	1.99	51	24	9	0.72	1.07	200/61
TTSH-175-150	1¾	45	2.24	57	24	10.5	0.79	1.18	200/61
TTSH-200-150	2	51	2.56	65	24	12	0.93	1.38	200/61
TTSH-250-150	2½	62	3.11	79	24	15	1.39	2.07	200/61
TTSH-300-150	3	76	3.62	92	24	18	1.85	2.75	200/61
TTSH-350-150	3½	90	4.25	108	24	21	2.93	4.36	200/61
TTSH-400-150	4	102	4.72	120	24	24	2.93	4.36	200/61
TTSH-600-150	6	152	6.98	179	24	36	4.43	6.59	100/30.5
TTSH-800-150	8	203	9.25	235	24	48	6.20	9.23	100/30.5