



Sludge & Debris Vacuum Hose

Four sizes from 4" to 10", rated 87 PSI working and 261 PSI burst, full vacuum at 29 in.Hg. -40 °F to +160 °F, in 200 ft coils at 4" and 100 ft above. Yellow or white tube.

Application:

Heavy duty bulk material suction and discharge for ultra-abrasive materials mounting on trucks and vacuum equipment. 5/16" tube designed for higher abrasion with cutting edge, tearing and wear from abrasive media.

Tube:

Yellow or white smooth pure gum rubber, 1/4" or 5/16" thick, ultra-resistant to abrasion

Reinforcement:

High-tensile textile plies, embedded helix wire, antistatic wire

Cover:

Green corrugated rubber with fabric impression, weather and abrasion resistant

Working pressure:

87 PSI

Nominal burst pressure:

261 PSI, 18 bar

Vacuum rating:

29 in.Hg

Temperature:

-40°F to +160°F (-40°C to +71°C)

Marking:




Made in two versions: the yellow tube for higher-abrasion materials with cutting edges, the white tube for materials that may need FDA approval, such as PVC granules and grain.

PART NO.	ID		OD		W.P.	Burst	Vacuum	Weight		Max. L
	Inch	mm	Inch	mm	PSI	PSI	In.Hg	lbs/ft	Kg/m	ft/m
SLYG-400-87	4"	102	5.04	128	87	261	29	5.1	7.59	200/61
SLYG-600-87	6"	152	7.09	180	87	261	29	6.08	9.05	100/30.5
SLYG-800-87	8"	203	9.2	234	87	261	29	8.95	13.32	100/30.5
SLYG-1000-87	10"	254	11.2	284	87	261	29	11.2	16.67	100/30.5