



PETROLEUM HOSE

Corrugated Tank Truck Oil Suction & Discharge Hose

Application:

Corrugated suction and discharge hose designed for transfer of petroleum and fuel from tank to tank trucks and vice versa in fuel stations. It is light weight, easy to handle and flexible hose.

Tube:

Black smooth rubber suitable for mineral oil and all grades of petroleum products with up to 50% aromatic content and unleaded petrol with maximum 5% MTBE and 15% oxygenated compounds.

Reinforcement:

High tensile textile plies, helix wire embedded and antistatic wire.

Cover:

Black, corrugated surface, conductive, resistant to abrasion, oil, fuel, ozone and weather conditions. Flame resistant according to TRbF 131-Teil 2 # 5.5. Fabric impression.

Working Pressure:

150 PSI, 10 bar

Nominal Burst Pressure:

450 PSI, 30 bar

Temperature:

-22°F/+194°F (-30°C /+90°C)

Marking:

iPARAGON



PART NO.	ID		OD		Vacuum	Min. b. r.	Weight		Max. L
	Inch	mm	Inch	mm	In.hg	Inch	Lbs./ft	Kg/m	ft /m
TTCH-100-150	1	25	1.41	36	24	2	0.47	0.70	200/61
TTCH-125-150	1¼	32	1.69	43	24	2.5	0.50	0.75	200/61
TTCH-150-150	1½	38	1.99	51	24	3.5	0.67	1.00	200/61
TTCH-200-150	2	51	2.56	65	24	5	0.94	1.40	200/61
TTCH-250-150	2½	63	3.11	79	24	6	1.28	1.90	200/61
TTCH-300-150	3	76	3.62	92	24	8	1.61	2.40	200/61
TTCH-400-150	4	102	4.72	120	24	10	2.49	3.70	200/61
TTCH-500-150	5	127	6.98	179	24	14	3.02	4.50	100/30.5
TTCH-600-150	6	152	9.25	235	24	16	4.44	6.60	100/30.5