

Mill Hose

Single/Double Jacket Mill Discharge Hose 250psi

Application:

Used in open ended water discharge, wash down, and construction pump applications only.

This hose is not intended for firefighting applications

Color:

White

Reinforcement:

Nitrile rubber

Jacket:

100% virgin high tenacity polyester, single jacket up to 2 3/4" and double jacket 3" up, standard wall thickness.

Fitting Type:

Expansion Ring, NST (NH)

Working Pressure:

250 PSI, 17 bar

Nominal Burst Pressure:

750 PSI, 51 bar

Marking:

PARAGON



 PART NO.	 Inner Diameter		 Service Pressure		 Min. Burst Pressure		 Max. L
	Inch	mm	PSI	Bar	PSI	Bar	ft/m
SJMH-150-250-LL	1 1/2	38	250	17	750	51	100/30
SJMH-175-250-LL	1 3/4	45	250	17	750	51	100/30
SJMH-200-250-LL	2	50	250	17	750	51	100/30
SJMH-250-250-LL	2 1/2	65	250	17	750	51	100/30
SJMH-275-250-LL	2 3/4	70	250	17	750	51	100/30
*SJMH-300-250-LL	3	75	250	17	750	51	100/30
*SJMH-400-250-LL	4	102	250	17	750	51	100/30
*SJMH-600-250-LL	6	152	250	17	750	51	100/30

3", 4" and 6" are double jacket hose

Hose assembly available with aluminum camlocks.