



FOOD HOSE

Wine/spirits suction & discharge hose

Heavy duty

Application:

Designed for low temperature heavy duty suction and delivery of high quality liquids & foodstuffs compatible with PVC.

Tube:

PVC Smooth

Structure:

Flexible hose made out of phthalate-free, very soft, low temperature resistant, food-grade PVC wall in accordance with the modified EU regulation 10/2011, reinforced with shock resistant PVC spiral.


Cover:

Smooth cover

Temperature:

-13°F/+131°F (-25°C / +55°C)

Phthalate-free, low temperature, heavy duty flexible hose for suction and delivery of liquids & foodstuffs



Phthalate Free!

PART NO.	ID		OD		w.p.	Vacc.	Min. b. r.	Weight		Max. L
	Inch	mm	Inch	mm	Psi	In. hg	Inch	Lb/ft	Kg/m	ft/m
SWPH-150	1½	40	1.9	50.4	145	28	7.87	6.29	9.36	82 / 25
SWPH-200	2	51	2.4	62.6	116	28	9.84	8.89	13.23	82 / 25
SWPH-225	2¼	60	2.8	72.0	118	26.5	11.02	11.24	16.73	82 / 25
SWPH-250	2½	63	2.9	75.4	101	26.5	11.41	11.82	17.59	82 / 25
SWPH-275	2¾	70	3.2	82.4	101	26.5	12.20	13.48	20.06	82 / 25
SWPH-300	3	76	3.5	89.0	101	26.5	13.77	14.82	22.05	82 / 25
SWPH-325	3¼	80	3.6	93.0	101	26.5	14.56	16.31	24.27	82 / 25
SWPH-350	3½	90	4.0	103.4	72	26.5	16.14	18.89	28.11	82 / 25
SWPH-400	4	102	4.5	116	72	26.5	18.89	22.24	33.09	82 / 25
SWPH-500	5	120	5.3	136.4	72	25	25.19	29.65	44.12	82 / 25
SWPH-600	6	152	6.9	176.0	43	25	29.52	45.56	67.79	82 / 25



FOOD HOSE

Wine/ spirits suction & discharge hose

Application:

Designed for medium duty suction and delivery of high quality liquids and foodstuffs, such as fruit juice, wine, beer and alcohol up to 50% compatible with PVC.

Tube:


PVC Smooth

Structure:

Flexible hose made out of phthalate-free, very soft, food-grade PVC wall in accordance with the modified EU regulation 10/2011, reinforced with shock resistant PVC spiral.

Cover:

Smooth cover



Temperature:

-23°F/+140°F (-25°C / +60°C)

Phthalate-free medium duty flexible hose for suction and delivery of liquids and foodstuffs



Phthalate Free!

PART NO.	ID		OD		w. p.	Vacc.	Min. b. r.	Weight		Max. L
	Inch	mm	Inch	mm	Psi	In. hg	Inch	Lb/ft	Kg/m	ft/m
WPH-125	1 ¼	35	1.6	43.0	130	13	8.8	4.26	6.34	82 / 25
WPH-150	1 ½	40	1.9	48.6	130	13	10.2	5.4	8.04	82 / 25
WPH-200	2	51	2.3	60.0	116	13	10.6	7.5	11.16	82 / 25
WPH-212	2 1/8	55	2.5	64.2	116	12.3	11.0	8.1	12.05	82 / 25
WPH-225	2 ¼	60	2.7	69.4	116	12.3	11.8	8.9	13.24	82 / 25
WPH-250	2 ½	63	2.8	72.3	101	12.3	12.7	10.3	15.33	82 / 25
WPH-275	2 ¾	70	3.1	80.2	101	12.3	14.9	11.9	17.71	82 / 25
WPH-325	3 ¼	80	3.6	92.0	101	12.3	15.7	13.5	20.09	82 / 25
WPH-350	3 ½	90	4.0	103.0	72	12.3	17.7	15.9	23.66	82 / 25
WPH-400	4	102	4.5	116.0	58	12.3	19.6	20.3	30.21	82 / 25
WPH-425	4 ¼	110	4.8	124.4	58	11.6	20.8	22.5	33.48	82 / 25
WPH-500	5	120	5.3	136.0	58	11.6	23.6	25.8	38.39	82 / 25
WPH-600	6	152	6.6	168.0	43	11.6	29.5	37.0	55.06	82 / 25