

# Petroleum hose BOP 3000psi

**Application:**

General application where flame resistance is required.  
Hydraulic BOP control line.

**Tube:**

Black oil resistant NBR.

**Reinforcement:**

Two high tensile steel wires braided.

**Cover:**

Thick red synthetic high temperature and flame resistant rubber.

**Temperature:**

-40°F/+250°F (-40°C /+ 121°C)

**Safety factor:**

1:4

**Marking:**

PARAGON



PART NO.	ID		OD		Pressure		Min. b. r.	Weight		Max. L
	Inch	mm	Inch	mm	Psi Working	Psi Nominal burst		Inch	Lb/ft	
FBOP-06-3000	3/8"	10	1"	25.4	3000	12000	2.56	0.54	0.8	200/61
FBOP-08-3000	1/2"	13	1.12	28.45	3000	12000	3.54	0.64	0.95	200/61
FBOP-12-3000	3/4"	19	1.37	34.8	3000	12000	4.72	1.22	1.8	200/61
FBOP-16-3000	1"	25.4	1.66	42.2	3000	12000	5.9	1.67	2.47	200/61



# Petroleum hose BOP 5000psi

**Application:**

General application where flame resistance is required.  
Hydraulic BOP control line.

**Tube:**

Oil resistant synthetic rubber.

**Reinforcement:**

Four high tensile steel wires spiral.

**Cover:**

Thick red synthetic high temperature and flame-resistant rubber.

**Temperature:**

-40°F/+250°F (-40°C /+ 121°C)

**Safety factor:**

1:4

**Marking:**

 PARAGON



PART NO.	ID		OD		Pressure		Min. b. r. Inch	Weight		Max. L ft/m
	Inch	mm	Inch	mm	Psi Working	Psi Nominal burst		Lb/ft	Kg/m	
BLR5D-10-C	1/2	12.5	1.04	26.4	5000	20000	7.09	0.61	0.9	200/61
BLR5D-14-C	3/4	19	1.31	33.2	5000	20000	11.02	1.15	1.7	200/61
BLR5D-20-C	1"	25	1.69	43	5000	20000	13.39	1.49	2.2	200/61
BLR5D-24-C	1 1/2"	38	2.4	61	5000	20000	18.11	3.31	4.9	100/30.5
BLR5D-32-C	2"	51	3.0	76.1	5000	20000	23.62	4.8	7.1	100/30.5

