



CONCRETE HOSE

Concrete Steel Wire Hose 1233PSI

Application:

Mandrel built steel wire reinforced concrete placement hose. Suitable for SCC (Self Compacting Concrete). Available on standard lengths, custom built lengths complete with swaged full flow Victaulic fittings, hardened at 62 / 64 HRC.

Tube:

Black smooth conductive rubber, resistant to abrasion.

Reinforcement:

High strength brass coated spiral steel wires.

Cover:

Black, smooth, conductive rubber, resistant to weather and abrasion. Fabric impression.

Working Pressure:

1233 PSI, 85 bar

Nominal Burst Pressure:

Safety factor 2:1

Vacuum

23.94 in. Hg





Temperature:

-40°F/+158°F (-40°C /+70°C)

Marking:

 PARAGON



 PART NO.	 Inner Diameter		 Outside Diameter		 Weight		No Wire Nr
	Inch	mm	Inch	mm	Lbs./Ft	Kg/m	
CPSH-200-1233	2"	51	2.75"	70	1.7	2.53	4
CPSH-250-1233	2.5"	63	3.42"	87	2.6	3.87	4
CPSH-300-1233	3"	76	3.97"	101	3.8	5.65	4
CPSH-400/1-1233	4"	102	4.84"	123	4.6	6.84	4
CPSH-400/2-1233	4"	102	5.03"	128	5.1	7.59	4
CPSH-500/1-1233	5"	127	5.90"	150	5.8	8.63	4
CPSH-500/2-1233	5"	127	6.10"	155	6.5	9.67	4