Fuel Drop Hose

Application:
Light, flexible collecting hose for oil and petroleum products with up to 50% aromatic content. Its outer thermoplastic helix resists abrasion and slides easily.

Tube:
Black NBR, conductive

Reinforcement:
Synthetic plies, anti-static wire

Cover:
Black corrugated, with a green outer thermoplastic helix cover. Ozone and oil resistant

Size range:
1½" – 4" (38 mm – 102 mm)

Working pressure:
150 PSI

Temperature:
−13°F to +176°F (−25°C to +80°C)

Best for:
Collecting and dropping fuel and oil from tankers and storage

Marking:
PARAGON



PART NUMBER	ID		WORKING PRESSURE		BURST PRESSURE		VACUUM	BEND RADIUS		WEIGHT		COIL LENGTH	
	in	mm	PSI	bar	PSI	bar	in.Hg	in	mm	lb/ft	kg/m	ft	m
FUDR-150-150	1½"	38	150	10	450	31	13	3.15	80	0.78	1.16	100	30.5
FUDR-200-150	2"	51	150	10	450	31	13	3.94	100	1.05	1.56	100	30.5
FUDR-250-150	2½"	64	150	10	450	31	11.5	5.12	130	1.27	1.89	100	30.5
FUDR-300-150	3"	76	150	10	450	31	11.5	5.91	150	1.54	2.29	50	15.2
FUDR-400-150	4"	102	150	10	450	31	10	7.87	200	1.99	2.96	50	15.2