

RUBBER & PLASTIC SEALS

Application:

Suitable for the sealing of medium like hydraulic oil, corrosive solvent (such as strong acid and strong alkali), steam and water, etc. The products widely apply to petrochemical, construction machinery, coal mining machinery, food machinery, electrical equipment, metallurgical equipment, refrigeration equipment, shields machine and other industries.

Product Feature:

High temperature resistance, corrosion resistance, oil resistance, food grade product

Material:

NBR/HNBR/EPDM/FKM

Temperature Range:

-67°F~/+392°F (-55C~/+200C)



HAMMER UNIONS



FIGURE 602 THREADED 6000 PSI CWP

Specially designed lip type elastomer seal protects metal to metal sealing surface and reduces line flow turbulence

Size (Inch.)	Weight Each (LBS)	Standard Carton
1	3.74	4
2	12.87	4
3	22.75	2
4	36.96	1



FIGURE 602 BUTT WELD 6000 PSI CWP

Specially designed lip type elastomer seal protects metal to metal sealing surface and reduces line flow turbulence

Size (Inch.)	Weight Each (LBS)	Standard Carton
2	13.82	4
3	26.25	2
4	37.82	1



FIGURE 1002 BUTT WELD 10,000 PSI CWP

Specially designed lip type elastomer seal protects metal to metal sealing surface and reduces line flow turbulence

Size (Inch.)	Weight Each (LBS)	Standard Carton
2	13.93	4
3	25.74	2
4	37.42	1



FIGURE 1502 BUTT WELD 15,000 PSI CWP

Specially designed lip type elastomer seal protects metal to metal sealing surface and reduces line flow turbulence

Size (Inch.)	Weight Each (LBS)	Standard Carton
2	19.95	2
3	29.04	2
4	78.39	1