

PRESSURE WASHER HOSE 1 Wire And 2Wire Pressure Washer Hose

Application:

Medium pressure service per table below with high temperature of water. oil, fuel, weather, ozone and abrasion resistant.

Tube:

Synthetic rubber black tube.

Reinforcement:

One or Two high tensile steel wire compact braid reinforcement.

Cover:

Synthetic rubber black or gray outer cover.



Temperature:

-40°F/+212°F (-40°C /+100°C)

Max operating temp. +257°F (+125°C)

Air max+160°F (+70°C)

Operating temp. in excess of +212°F (+100°C)

May materially reduce the life of the hose.

ambient-40°F/+175°F (-40°C /+80°C)

Marking:

 PARAGON

As a Canadian manufacturer of high performance 1 & 2 wire pressure washer hose, we can accommodate any specific requirements you may desire.

1/4", 3/8" & 1/2" PROWASH I & II

MEET OR EXCEED THE REQUIREMENT OF SAE J517 EN 857 ISC

MEET FLAME RESISTANCE ACCEPT AND DESIGNATION US MSHA IC-152/I

 PART NO. 1 WIRE	 ID Inch mm	 OD Inch mm	 W.P. Psi	 B.P. Psi	 Min. b. r. Inch	 Weight Lb/C ff Kg/m	 Max. L ft/m
PWB1-025-50'	1/4 6	0.48 12	5000	15000	2.0	11	
PWB1-0375-50'	3/8 9.5	0.63 16	4000	12500	2.5	18	
PWB1-050-50'	1/2 12.5	0.75 19	3000	10000	3.5	27	

 PART NO. 2 WIRE	 ID Inch mm	 OD Inch mm	 W.P. Psi	 B.P. Psi	 Min. b. r. Inch	 Weight Lb/C ff Kg/m	 Max. L ft/m
PWB2-025-50'	1/4 6	0.48 12	7000	24000	2.0	11	
PWB2-0375-50'	3/8 9.5	0.63 16	6000	20000	2.5	18	
PWB2-050-50'	1/2 12.5	0.75 19	4500	18000	3.5	27	

Features:

- Smaller OD, lower profile, takes up less space on reels
- Extraordinary flexibility, superior flex impulse performance
- Less weight, easier to handle and routing
- Excellent bend radii
- Longer service life

