

WATER HOSE

Premium Heavy Duty PVC/NITRILE Discharge Hose

Application:

Agriculture
Construction
Industrial wash-down
Mining and dewatering

Irrigation
Limited oil and chemical
Water pump discharge
Cable covering

Temperature:

-20°F/+176°F (-29°C /+80°C)

Marking:

PARAGON







Tube and Cover:

Black PVC/Nitrile material extruded in one stage.

Reinforcement:

High tensile polyester yarn reinforcement.



 PART NO.	 Inner Diameter		 Wall Thickness		 Pressure	 Weight		 Max. L
	Inch	mm	Inch	mm	Psi in 60°F	Lbs./Ft	Kg/m	ft/m
BKFW-150-300-200	1½	38	0.07	1.8	300	0.20	0.30	200/61
BKFW-200-220-200	2	51	0.07	1.8	220	0.27	0.40	200/61
BKFW-250-200-200	2½	63	0.09	2.3	200	0.38	0.57	200/61
BKFW-300-175-200	3	76	0.09	2.3	175	0.48	0.71	200/61
BKFW-400-150-200	4	102	0.09	2.3	150	0.71	1.06	200/61
BKFW-600-150-200	6	152	0.12	3.0	150	1.08	1.61	200/61
BKFW-800-150-200	8	203	0.13	3.3	150	1.85	2.75	200/61
BKFW-1000-150-200	10	254	0.15	3.8	150	2.86	4.26	200/61

Longer length available on request.