



PETROLEUM HOSE

Tank Truck Suction & Discharge Hose 300PSI

Application:

Oil suction and discharge hose suitable for petroleum products.

Tube:

Black smooth synthetic rubber, resistant to mineral oils and fuels with maximum 50% aromatic content.

Reinforcement:

High tensile textile plies and helix wire embedded and antistatic wire.

Cover:

Black, smooth conductive rubber, abrasion, oil, fuel, ozone and weather resistant. Flame resistant according TRbF – 131 – Teil 2 - § 5.5.

Working Pressure:

300 PSI, 20 bar

Nominal Burst Pressure:

900 PSI, 60 bar

Temperature:

-22°F/+194°F (-30°C /+90°C)

Marking:

 PARAGON



PART NO.	ID		OD		Vacuum	Min. b. r.	Weight		Max. L
	Inch	mm	Inch	mm	In. hg	Inch	Lbs./ft	Kg/m	ft /m
TTSH-200-300	2	51	2.60	66	30	8	1.30	1.38	200/61
TTSH-300-300	3	76	3.62	92	30	12	2.06	2.75	200/61
TTSH-400-300	4	102	4.72	120	30	18	3.05	4.36	200/61
TTSH-600-300	6	152	6.88	175	30	42	5.95	6.59	100/30.5