



WATER HOSE

Low temperature PVC water suction and discharge hose

Application:

High flexible hose in sub-zero temperature, use for construction pump. Septic tank and marine pumps in rental and dewatering. Resistance to some chemicals, mild acids and wastewater. Special compound of PVC material to increase flexibility at low temperatures.

Tube:

Smooth clear extra soft PVC.

Reinforcement:

Blue rigid PVC helix.

Cover:


Clear abrasion and weather resistant extra soft PVC.

Temperature:

-40°F/+150°F (-40°C /+65°C)

Marking:

 PARAGON



 PART NO.	 ID		 OD		 W.P.	 Vacuum	 Min. b. r.	 Weight		 Max. L
	Inch	mm	Inch	mm	Psi	In. hg	Inch	Lb/ft	Kg/m	ft/m
BPWH-075	3/4	19	0.95	24	90	29	3	0.16	0.24	100/30.5
BPWH-100	1	25	1.24	31	85	29	3	0.26	0.39	100/30.5
BPWH-125	1¼	32	1.54	39	80	29	4	0.34	0.51	100/30.5
BPWH-150	1½	38	1.81	46	70	29	5	0.44	0.65	100/30.5
BPWH-200	2	51	2.39	61	70	29	7	0.75	1.12	100/30.5
BPWH-250	2½	65	2.94	75	70	29	8	1.02	1.52	100/30.5
BPWH-300	3	75	3.43	87	65	29	10	1.21	1.80	100/30.5
BPWH-400	4	100	4.54	115	50	29	14	2.02	3.01	100/30.5
BPWH-600	6	150	6.67	169	35	28	23	3.70	5.51	100/30.5