Contractor Air & Water Hose 300 PSI

Ten sizes from ½″ to 4″, rated 300 PSI with a 3:1 burst margin and usable down to −31 °F

Application:
Mandrel-built heavy-duty hose for both compressed air and water, used on compressors, drilling equipment and standard pneumatic machines.

Tube:
Black smooth rubber

Reinforcement:
High tensile textile plies

Cover:
Yellow, smooth surface, fabric impression, weather and abrasion resistant

Size range:
1/2" – 4" (13 mm – 102 mm)

Working pressure:
300 PSI

Temperature:
-31°F to +176°F (-35°C to +80°C)

Best for:
Compressors, drilling equipment, and standard pneumatics

Marking:
PARAGON



PART NUMBER	ID		OD		WORKING PRESSURE		BURST PRESSURE		WEIGHT		COIL LENGTH	
	in	mm	in	mm	PSI	bar	PSI	bar	lb/ft	kg/m	ft	m
CAYW-050-300	1/2"	13	0.91	23	300	21	900	62	0.24	0.36	200	61
CAYW-0625-300	5/8"	16	1.02	26	300	21	900	62	0.28	0.42	200	61
CAYW-075-300	3/4"	19	1.18	30	300	21	900	62	0.34	0.51	200	61
CAYW-100-300	1"	25	1.46	37	300	21	900	62	0.48	0.71	200	61
CAYW-125-300	1-1/4"	32	1.73	44	300	21	900	62	0.58	0.86	200	61
CAYW-150-300	1-1/2"	38	2.01	51	300	21	900	62	0.75	1.12	200	61
CAYW-200-300	2"	51	2.6	66	300	21	900	62	1.16	1.73	200	61
CAYW-250-300	2-1/2"	64	3.11	79	300	21	900	62	1.49	2.22	200	61
CAYW-300-300	3"	76	3.62	92	300	21	900	62	1.67	2.49	200	61
CAYW-400-300	4"	102	4.65	118	300	21	900	62	2.18	3.24	200	61