HYDRAULIC HOSE

Hydraulic Hose SAE100R17

Application:
This hose is designed for hydraulic system and high peak pressures.
Meets flame resistance under MSHA standard.

Tube:
Oil resistant synthetic rubber.

Reinforcement:
One braid up to -10, Two braid -12 & -16.

Cover:
Black, synthetic rubber resistant to oils, abrasion and ozone.
Smooth cover.

Temperature:
-40°F/+212°F (-40°C /+100°C)

Marking:
PARAGON



PART NO.	ID		OD		Wire OD	W.P.	B.P.	Min. b. r.	Weight		Max. L
	Inch	mm	Inch	mm	mm	Psi	Psi	Inch	lbs./FT	Kg/m	ft/m
SR17-04	1/4	6.6	0.49	12.4	10.4	3000	12000	2	0.11	0.16	200/61
SR17-05	5/16	8.2	0.55	14.1	12	3000	12000	2.2	0.15	0.22	200/61
SR17-06	3/8	10	0.63	16	13.9	3000	12000	2.6	0.18	0.27	200/61
SR17-08	1/2	13	0.77	19.4	17.6	3000	12000	3.5	0.26	0.39	200/61
SR17-10	5/8	16.3	0.94	23.8	21.7	3000	12000	3.9	0.41	0.61	200/61
SR17-12	3/4	19.4	1.09	27.6	25.5	3000	12000	4.7	0.51	0.76	164/50
SR17-16	1	25.5	1.43	36.2	34	3200	12800	5.91	0.86	1.28	164/50