Orange PVC Water Suction & Discharge Hose

Application:
X Line PVC water suction and discharge hose for heavy-duty work that needs vacuum and higher working pressure together. Smooth bore with a corrugated outside.

Tube:
Flexible PVC, smooth bore

Reinforcement:
Rigid PVC helix and synthetic braiding

Cover:
Corrugated PVC surface

Size range:
1½" – 8" (38 mm – 203 mm)

Working pressure:
60–110 PSI by size

Temperature:
−13°F to +140°F (−25°C to +60°C)

Best for:
Heavy-duty water suction and discharge needing vacuum and pressure

Marking:
PARAGON



PART NUMBER	ID		OD		WORKING PRESSURE		VACUUM	BEND RADIUS		WEIGHT		LENGTH
	in	mm	in	mm	PSI	bar	in.Hg	in	mm	lb/ft	kg/m	
OPSH-150	1½"	38	2.1	53	110	8	28	2.5	64	0.47	0.7	60, 100 ft
OPSH-200	2"	51	2.6	66	100	7	28	4	102	0.7	1.04	60, 100 ft
OPSH-300	3"	76	3.7	94	100	7	28	6.3	160	1.13	1.68	60, 100 ft
OPSH-400	4"	102	4.8	122	75	5	28	7.1	180	1.74	2.59	60, 100 ft
OPSH-500	5"	127	6.1	155	70	5	28	9.2	234	2.9	4.32	60, 100 ft
OPSH-600	6"	152	7.2	183	70	5	28	10.2	259	3.88	5.77	60, 100 ft
OPSH-800	8"	203	9.5	241	60	4	28	15.7	399	5.54	8.24	15, 20, 25, 40 ft