



HOT WATER Steam Hose

Application:

Mandrel built steam hose designed for use with saturated steam up to 210 °C / 18 bar and peaks of superheated steam up to 232 °C / 18 bar. Complying with BS 5342 type 2A.

Tube:

Black smooth rubber, heat and steam resistant. specially developed to avoid cracking and hardening.

Reinforcement:

High tensile spiral wire.

Cover:

Red, smooth rubber, abrasion, ozone and weather resistant. Pin pricked to evacuate gases. Fabric impression.

Working Pressure:

270 PSI, 18 bar

Nominal Burst Pressure:

2700 PSI, 180 bar


Temperature:

-40°F/+450°F (-40°C /+232°C)

Marking:

 PARAGON



 PART NO.	 Inner Diameter		 Outside Diameter		 Weight		 Max. L
	Inch	mm	Inch	mm	Lb/Ft	Kg/m	ft/m
SWR-075-270	3/4	19	1.22	31	0.49	0.73	200/61
SWR-100-270	1	25	1.45	37	0.61	0.91	200/61
SWR-125-270	1¼	32	1.81	46	0.89	1.33	200/61
SWR-150-270	1½	38	2.04	52	1.05	1.57	200/61
SWR-200-270	2	51	2.59	66	1.51	2.25	200/61
SWR-250-270	2½	63	3.18	81	2.27	3.38	200/61
SWR-300-270	3	76	3.77	96	3.06	4.56	200/61
SWR-400-270	4	102	4.88	124	4.70	6.99	200/61