



PETROLEUM HOSE

Low Temp Tank Truck Suction & Discharge Hose

Application:

Tank Truck Oil suction and discharge hose suitable for petroleum products for extreme low temperature.

Tube:

Black, smooth, conductive, synthetic rubber, suitable for petroleum products with up to 50% aromatic.

Reinforcement:

High tensile textile plies and two helix wires embedded and antistatic wire.

Cover:

Black, smooth conductive rubber, abrasion, oil, fuel, ozone and weather resistant.

Working pressure:

150 PSI, 10 bar

Nominal burst pressure:

450 PSI, 30 bar








Temperature:

-65°F/+194°F (-54°C /+90°C)

Marking:

 PARAGON



 PART NO.	 ID		 OD		 Vacc.	 Min. b. r.	 Weight		 Max. L
	Inch	mm	Inch	mm	In. Hg	Inch	Lb/ft	Kg/m	ft / m
L TTC-200-150	2	51	2.48	63	24	7	1.18	1.75	100/30.5
L TTC-300-150	3	76	3.50	89	24	10	1.85	2.7	100/30.5
L TTC-400-150	4	102	4.57	116	24	14	2.77	4.1	100/30.5
L TTC-600-150	6	152	6.69	170	24	20	5.16	7.6	50/15.25
L TTC-800-150	8	203	8.86	225	24	26	8.26	12.2	50/15.25