Tank Truck Suction & Discharge Hose 300 PSI

Four sizes from 2″ to 6″, rated 300 PSI working and 900 PSI burst, with a full 30 in.Hg vacuum on every size. −22 °F to +194 °F, in 200 ft (61 m) coils — 100 ft (30.5 m) in 6″.

Application:
Oil suction and discharge hose for petroleum products, rated for full vacuum on the suction side of a tank-truck transfer.

Tube:
Black smooth synthetic rubber, resistant to mineral oils and fuels with maximum 50% aromatic content

Reinforcement:
High tensile textile plies and helix wire embedded and antistatic wire

Cover:
Black, smooth conductive rubber, abrasion, oil, fuel, ozone and weather resistant. Flame resistant according TRbF – 131 – Teil 2 - § 5.5

Size range:
2" – 6" (51 mm – 152 mm)

Working pressure:
300 PSI

Temperature:
−22°F to +194°F (−30°C to +90°C)

Best for:
Loading and unloading petroleum road tankers; fuel and oil transfer

Marking:
PARAGON



PART NUMBER	ID		OD		WORKING PRESSURE		BURST PRESSURE		VACUUM	BEND RADIUS		WEIGHT		COIL LENGTH	
	in	mm	in	mm	PSI	bar	PSI	bar	in.Hg	in	mm	lb/ft	kg/m	ft	m
TTSH-200-300	2"	51	2.6	66	300	21	900	62	30	8	203	1.3	1.93	200	61
TTSH-300-300	3"	76	3.62	92	300	21	900	62	30	12	305	2.06	3.07	200	61
TTSH-400-300	4"	102	4.72	120	300	21	900	62	30	18	457	3.05	4.54	200	61
TTSH-600-300	6"	152	6.88	175	300	21	900	62	30	42	1067	5.95	8.85	100	30.5