



VACUUM ABRASION HOSE

Sludge & Debris Vacuum Hose

Application:

Heavy duty bulk material suction and discharge for ultra-abrasive materials mounting on trucks and vacuum equipment. 5/16" tube designed for higher abrasion with cutting edge, tearing and wear from abrasive media.

Tube:

Yellow and white smooth pure gum rubber, ¼" and 5/16" tube thickness, ultra-resistant to abrasion.

Reinforcement:

High tensile textile plies, helix wire embedded, antistatic wire.

Cover:

Green, corrugated rubber, weather and abrasion resistant. Fabric impression.

Working pressure:

87 PSI, 6 Bar

Nominal burst pressure:

261 PSI, 6 Bar

Temperature:

-40°F/+160°F (-40°C /+71°C)

Marking:

PARAGON



Hoe is produced in 2 different versions. The yellow tube works for higher abrasion materials with cutting edge, and the white tube is suitable for abrasion material which may need FDA approval such as PVC granular and grains.

PART NO.	ID		OD		Vacc.	Weight		Max. L
	Inch	mm	Inch	mm		lbs./ft	Kg/m	
SLYG-400-87	4	102	128	5.04	29	5.10	3.42	200/61
SLYG-600-87	6	152	180	7.09	29	6.08	4.09	100/30.5
SLYG-800-87	8	203	236	9.20	29	8.95	6.01	100/30.5
SLYG-1000-87	10	254	288	11.20	29	11.20	7.53	100/30.5