Steam Cleaner Hose

High performance steam hose for cleaner machines and pressure washers equipment

Application:
High-performance steam hose for steam-cleaner machines and pressure-washer equipment, rated for both steam and hot water. Not recommended for cold water.

Tube:
Black smooth rubber, heat and steam resistant. Specially developed to avoid cracking and hardening

Reinforcement:
High tensile steel wire braided

Cover:
Black, smooth finish cover, abrasion, heat, ozone, and weather resistant. Pin pricked to evacuate gases. Fabric impression

Size range:
⅜" – ½" (10 mm – 13 mm)

Working pressure:
Steam 350 / water 2500–3000 PSI

Temperature:
Steam +325°F / hot water +250°F

Best for:
Steam cleaners and pressure-washer equipment

Marking:



PART NUMBER	ID		OD		WORKING PRESSURE		WEIGHT		COIL LENGTH	
	in	mm	in	mm	PSI	bar	lb/ft	kg/m	ft	m
SCHB-0375-350	⅜"	10	0.69	18	350	24	0.23	0.34	200	61
SCHB-050-350	½"	13	0.82	21	350	24	0.32	0.48	200	61

Steam: 350 PSI at +325 °F; safety factor 10:1.

Hot water: 3000 PSI at +250 °F (⅜″), 2500 PSI at +250 °F (½″); safety factor 4:1.

Steam –40 °F to +325 °F (–40 °C to +163 °C); hot water –40 °F to +250 °F (–40 °C to +121 °C). Not recommended for cold water.