Green PVC Water Suction & Discharge Hose

Economical clear-PVC suction hose for irrigation, liquid fertilizer and air-seeder lines

Application:
Economical, flexible clear-PVC suction hose for agricultural liquid fertilizer, air-seeder lines, irrigation and general water suction and discharge. Resistant to some chemicals and light acids.

Tube:
Smooth clear PVC

Reinforcement:
Green rigid PVC helix

Cover:
Clear abrasion and weather resistant PVC

Size range:
¾" – 8" (19 mm – 203 mm)

Working pressure:
25–90 PSI by size

Temperature:
−5°F to +150°F (−20°C to +65°C)

Best for:
Liquid fertilizer, air-seeder lines, irrigation, water suction and discharge

Marking:



PART NUMBER	ID		OD		WORKING PRESSURE		VACUUM	BEND RADIUS		WEIGHT		COIL LENGTH	
	in	mm	in	mm	PSI	bar	in.Hg	in	mm	lb/ft	kg/m	ft	m
GPWH-075	¾"	19	0.95	24	90	6	29	3	76	0.16	0.24	100	30.5
GPWH-100	1"	25	1.24	31	85	6	29	3	76	0.26	0.39	100	30.5
GPWH-125	1¼"	32	1.54	39	80	6	29	4	102	0.34	0.51	100	30.5
GPWH-150	1½"	38	1.81	46	70	5	29	5	127	0.44	0.65	100	30.5
GPWH-200	2"	51	2.29	58	65	4	29	7	178	0.57	0.85	100	30.5
GPWH-250	2½"	64	2.85	72	60	4	29	8	203	0.87	1.29	100	30.5
GPWH-300	3"	76	3.43	87	60	4	29	10	254	1.21	1.8	100	30.5
GPWH-400	4"	102	4.45	113	50	3	29	14	356	1.78	2.65	100	30.5
GPWH-600	6"	152	6.67	169	35	2	28	23	584	3.7	5.51	100	30.5
GPWH-800	8"	203	8.82	224	25	2	28	30	762	6.7	9.97	20	6.1