Tank Truck Discharge Hose

Application:
Oil discharge hose for petroleum products.

Tube:
Black smooth synthetic rubber, resistant to mineral oils and fuels with maximum 50% aromatic content

Reinforcement:
High tensile textile plies embedded with antistatic wire

Cover:
Red, smooth conductive rubber, abrasion, oil, fuel, ozone and weather resistant

Size range:
1½" – 6" (38 mm – 152 mm)

Working pressure:
150 PSI

Temperature:
−22°F to +194°F (−30°C to +90°C)

Best for:
Oil and petroleum product discharge from tank trucks

Marking:
PARAGON



PART NUMBER	ID		OD		WORKING PRESSURE		BURST PRESSURE		WEIGHT		COIL LENGTH	
	in	mm	in	mm	PSI	bar	PSI	bar	lb/ft	kg/m	ft	m
TTDH-150-300	1½"	38	1.81	46	150	10	450	31	0.77	1.15	200	61
TTDH-200-300	2"	51	2.4	61	150	10	450	31	0.82	1.22	200	61
TTDH-300-300	3"	76	3.42	87	150	10	450	31	1.42	2.11	200	61
TTDH-400-300	4"	102	4.49	114	150	10	450	31	1.92	2.86	200	61
TTDH-600-300	6"	152	6.45	164	150	10	450	31	3.6	5.36	100	30.5