

PRESSURE WASHER HOSE 1 Wire And 2 Wire Pressure Washer Hose

Application:

Designed for high pressure cleaning applications. Oil, fuel, weather, ozone and abrasion resistant.

Tube:

Synthetic black rubber tube.

Reinforcement:

One or two high tensile steel wire compact braid reinforcement.

Cover:

Synthetic rubber black or gray outer cover.

Temperature:

-40°F/+212°F (-40°C /+100°C)

Max operating temp. +257°F (+125°C)

Air max+160°F (+70°C)

Operating temp. more than +212°F (+100°C) may reduce the life of the hose.

Ambient -40°F/+175°F (-40°C /+80°C)

Marking:

PARAGON

As a Canadian manufacturer of high performance 1 & 2 wire pressure washer hose, we can accommodate any specific requirements you may desire.



1/4" 3/8" & 1/2" PROWASH I & II

MEET OR EXCEEDS THE REQUIREMENT OF SAE J517 EN 857 1SC
 MEET FLAME RESISTANCE AND DESIGNATION US MSHA IC-152/1

 PART NO. 1 WIRE	 ID		 OD		 W. P.	 B. P.	 Min. b. r.	 Max. L
	Inch	mm	Inch	mm	Psi	Psi	Inch	ft/m
PWB1-025-50'	¼	6	0.48	12	5000	15000	2.0	25', 50', 75',100'
PWB1-0375-50'	¾	9.5	0.63	16	4000	12500	2.5	25', 50', 75',100'
PWB1-050-50'	½	12.5	0.75	19	3000	10000	3.5	25', 50', 75',100'

 PART NO. 2 WIRE	 ID		 OD		 W. P.	 B. P.	 Min. b. r.	 Max. L
	Inch	mm	Inch	mm	Psi	Psi	Inch	ft/m
PWB2-025-50'	¼	6	0.48	12	7000	24000	2.0	25', 50', 75',100'
PWB2-0375-50'	¾	9.5	0.63	16	6000	18000	2.5	25', 50', 75',100'
PWB2-050-50'	½	12.5	0.75	19	4500	12500	3.5	25', 50', 75',100'

Features:

- Smaller OD, lower profile, takes up less space on reels
- High flexibility, superior flex impulse performance
- Less weight, easier to handle and routing
- Excellent bend radius
- Longer service life

