Hard Wall Marine Exhaust Hose

Application:
Wet exhaust hose for marine craft engines. Also used for suction and discharge of fuel, oil and hydraulic fluid where unusual sizes are needed.

Tube:
Black NBR, exhaust gas, fuel and fire resistant

Reinforcement:
High tensile textile cords with flexible steel helix wire

Cover:
Black NBR, ozone, hydrocarbon and fire resistant

Size range:
⅝" – 4" (16 mm – 102 mm)

Working pressure:
30 PSI

Temperature:
−4°F to +212°F (−20°C to +100°C)

Best for:
Marine engine wet exhaust; fuel, oil and hydraulic fluid in odd sizes

Marking:
PARAGON



PART NUMBER	ID		OD		WORKING PRESSURE		BURST PRESSURE		VACUUM	BEND RADIUS		WEIGHT	
	in	mm	in	mm	PSI	bar	PSI	bar	in.Hg	in	mm	lb/ft	kg/m
MEH-0625-30	⅝"	16	1.02	26	30	2	90	6	30	2	51	0.36	0.54
MEH-075-30	¾"	19	1.14	29	30	2	90	6	30	2.25	57	0.45	0.67
MEH-0875-30	⅞"	22	1.26	32	30	2	90	6	30	2.75	70	0.49	0.73
MEH-100-30	1"	25	1.38	35	30	2	90	6	30	3	76	0.55	0.82
MEH-1125-30	1⅛"	29	1.5	38	30	2	90	6	30	3.25	83	0.6	0.89
MEH-150-30	1½"	38	1.89	48	30	2	90	6	30	4.5	114	0.7	1.04
MEH-175-30	1¾"	44	2.2	56	30	2	90	6	30	5.25	133	0.86	1.28
MEH-200-30	2"	51	2.44	62	30	2	90	6	30	6	152	0.98	1.46
MEH-250-30	2½"	64	2.87	73	30	2	90	6	27	7.5	190	1.32	1.96
MEH-300-30	3"	76	3.39	86	30	2	90	6	27	9	229	1.53	2.28
MEH-350-30	3½"	89	3.94	100	30	2	90	6	27	10.5	267	1.9	2.83
MEH-400-30	4"	102	4.41	112	30	2	90	6	27	12	305	2.12	3.15