

# LEADER LINE HYDRAULIC HOSE

### Application:

This hose designed for hydraulic system and high peak pressures. Meet flame resistance under MSHA standard.

### Tube:

Synthetic Rubber, suitable for water and oil. High tensile textiles plies, embedded antistatic Helix Wire.

### Reinforcement:

Two braids of antistatic high tensile helix wire.

### Cover:

Black, synthetic rubber resistant to oils, abrasion, and ozone. Smooth cover.

### Temperature:

-40°F/+212°F (-40°C /+100°C)

### Fittings:

Male NPT by Female Swivel

### Marking:

PARAGON



PART NO.	ID		OD		Wire OD	W.P.	B.P.	Min. b. r.	Weight		Max. L
	Inch	mm	Inch	mm	mm	Psi	Psi	Inch	Lb/FT	Kg/m	ft/m
SLR16-08	1/2	12.70	0.80	20	18.4	4250	17000	3.54	0.35	0.52	200/61
SLR16-12	3/4	19.05	1.10	28	25.8	3200	12800	4.72	0.59	0.88	164/50
SLR17-16	1 R17	25.40	1.43	36	34.0	3200	12800	5.91	0.86	1.28	164/50

Length	Part Number with NPT Male & Swivel Female		
	1/2"	3/4"	1"
10'	SLR16-08-10-MFNPT	SLR16-12-10-MFNPT	SLR17-16-10-MFNPT
15'	SLR16-08-15-MFNPT	SLR16-12-15-MFNPT	SLR17-16-15-MFNPT
20'	SLR16-08-20-MFNPT	SLR16-12-20-MFNPT	SLR17-16-20-MFNPT
25'	SLR16-08-25-MFNPT	SLR16-12-25-MFNPT	SLR17-16-25-MFNPT
30'	SLR16-08-30-MFNPT	SLR16-12-30-MFNPT	SLR17-16-30-MFNPT
50'	SLR16-08-50-MFNPT	SLR16-12-50-MFNPT	SLR17-16-50-MFNPT

