High Temperature Tank Truck Hose

Application:
Tank truck hose for hot oil and glycol at up to 250°F (120°C), for in-plant and oil field operations.

Tube:
Heat resistant synthetic rubber compound

Reinforcement:
High tensile wire helix embedded in layers of textile cords

Cover:
Black corrugated, abrasion and oil resistant

Size range:
2" – 4" (51 mm – 102 mm)

Working pressure:
150 PSI (300 PSI on request)

Temperature:
Up to +250°F (+120°C)

Best for:
Hot oil and glycol transfer, in-plant and oil field

Marking:
PARAGON



PART NUMBER	ID		OD		WORKING PRESSURE		BURST PRESSURE		WEIGHT		COIL LENGTH	
	in	mm	in	mm	PSI	bar	PSI	bar	lb/ft	kg/m	ft	m
HTTC-200-150-LL	2"	51	2.52	64	150	10	450	31	0.94	1.4	200	61
HTTC-250-150-LL	2½"	64	3.03	77	150	10	450	31	1.28	1.9	200	61
HTTC-300-150-LL	3"	76	3.54	90	150	10	450	31	1.61	2.4	200	61
HTTC-400-150-LL	4"	102	4.61	117	150	10	450	31	2.49	3.71	200	61

LL in the part number is the length in feet: HTTC-200-150-50 is a 2″ × 50′ length.

300 PSI working pressure is available on request.