

## Mill Hose

### Single Jacket Mill Discharge Hose 250psi

**Application:**

Used in open ended water discharge, wash down, and construction pump applications only.  
\*This hose is not intended for firefighting applications\*

**Color:**

White

**Reinforcement:**

Nitrile rubber

**Jacket:**

100% virgin high tenacity polyester, single jacket, standard wall thickness.

**Fitting Type:**

Expansion Ring, NST (NH)

**Working Pressure:**

250 PSI, 17 bar






**Nominal Burst Pressure:**

750 PSI, 51 bar

**Marking:**

 PARAGON



 PART NO.	 Inner Diameter		 Service Pressure		 Min. Burst Pressure		 Max. L
	Inch	mm	PSI	Bar	PSI	Bar	ft/m
SJMH-150-250-LL	1 1/2	38	250	17	750	51	100/30
SJMH-175-250-LL	1 3/4	45	250	17	750	51	100/30
SJMH-200-250-LL	2	50	250	17	750	51	100/30
SJMH-250-250-LL	2 1/2	65	250	17	750	51	100/30
SJMH-275-250-LL	2 3/4	70	250	17	750	51	100/30
SJMH-300-250-LL	3	75	250	17	750	51	100/30
SJMH-400-250-LL	4	102	250	17	750	51	100/30
SJMH-600-250-LL	6	152	250	17	750	51	100/30

Whip check cable recommended for safety