Low Temperature Fuel Discharge Hose

Application:
Fuel discharge hose for diesel, gasoline and other petroleum products in extreme cold.

Tube:
Black, smooth, conductive, synthetic rubber, suitable for petroleum products with up to 50% aromatic

Reinforcement:
High tensile textile plies and two helix wires embedded and antistatic wire

Cover:
Blue, smooth conductive rubber, abrasion, oil, fuel, ozone and weather resistant

Size range:
½" – 1" (13 mm – 25 mm)

Working pressure:
300 PSI

Temperature:
−65°F to +194°F (−54°C to +90°C)

Best for:
Diesel, gasoline and petroleum product transfer in extreme cold

Marking:
PARAGON



PART NUMBER	ID		OD		WORKING PRESSURE		BURST PRESSURE		VACUUM	WEIGHT		COIL LENGTH	
	in	mm	in	mm	PSI	bar	PSI	bar	in.Hg	lb/ft	kg/m	ft	m
LFDH-050-300	½"	13	0.83	21	300	21	900	62	24	1.18	1.76	100	30.5
LFDH-075-300	¾"	19	1.22	31	300	21	900	62	24	1.85	2.75	100	30.5
LFDH-100-300	1"	25	1.5	38	300	21	900	62	24	2.77	4.12	100	30.5