HYDRAULIC HOSE

Arctic Hydraulic Hose Exceeds SAE100R16

Application:
This hose is designed for hydraulic system and high peak pressures.
Meets flame resistance under MSHA standard.

Tube:
Oil resistant synthetic rubber.

Reinforcement:
Two braids of high tensile steel wire.

Cover:
Black, synthetic rubber resistant to oils, abrasion and ozone.
Smooth cover.

Temperature:
-67°F/+212°F (-55°C /+100°C)

Marking:
PARAGON



PART NO.	ID		OD		Wire OD	W.P.	B.P.	Min. b. r.	Weight		Max. L
	Inch	mm	Inch	mm	mm	Psi	Psi	Inch	lbs./FT	Kg/m	ft/m
LR16-04	1/4	6	0.51	13	11.3	5800	23200	1.96	0.17	0.25	200/61
LR16-06	3/8	10	0.66	17	15.1	4785	19140	2.56	0.26	0.39	200/61
LR16-08	1/2	13	0.80	20.5	18.4	4250	17000	3.54	0.35	0.52	200/61
LR16-10	5/8	16	0.94	24	21.9	3650	14600	3.93	0.47	0.70	200/61
LR16-12	3/4	19	1.10	28	25.8	3200	12800	4.72	0.59	0.88	164/50
LR16-16	1	25	1.39	35.5	32.8	2400	9600	5.91	0.78	1.16	164/50

MAGNIFAX
Industrial & Hydraulic Hoses
Accessories & Hose Fittings