



WATER HOSE

Green PVC water suction and discharge hose

Application:

An economical flexible hose for agricultural liquid fertilizer, air seeder lines, irrigation and water suction and discharge. This hose is resistance to some chemical and light acid.

Temperature:

-5°F/+150°F (-20°C /+65°C)

Marking:

 PARAGON

Tube:

Smooth clear PVC.









Reinforcement:

Green rigid PVC helix.

Cover:

Clear abrasion and weather resistant PVC.



 PART NO.	 ID		 OD		 W.P.	 Vacuum	 Min. b. r.	 Weight		 Max. L
	Inch	mm	Inch	mm	Psi	In. hg	Inch	Lbs./ft	Kg/m	ft/m
GPWH-075	3/4	19	0.95	24	90	29	2	0.16	0.24	100/30.5
GPWH-100	1	25	1.24	31	85	29	3	0.26	0.39	100/30.5
GPWH-125	1¼	32	1.54	39	80	29	4	0.34	0.51	100/30.5
GPWH-150	1½	38	1.81	46	70	29	6	0.44	0.65	100/30.5
GPWH-200	2	51	2.29	61	65	29	5	0.57	0.85	100/30.5
GPWH-250	2½	65	2.85	75	60	29	6	0.87	1.29	100/30.5
GPWH-300	3	75	3.43	87	60	29	12	1.21	1.80	100/30.5
GPWH-400	4	100	4.45	115	50	29	10	1.78	2.65	100/30.5
GPWH-600	6	150	6.67	169	35	28	25	3.70	5.51	100/30.5
GPWH-800	8	203	8.82	224	25	28	30	6.70	9.97	20/6