

CONCRETE HOSE

Grout & Plaster Hose

Application:

Mandrel built delivery hose for plaster, concrete, slurry, chalk and abrasive materials. Used on concrete machines for construction of tunnels and in public works.

Tube:

Black smooth conductive rubber, abrasion resistant.

Reinforcement:

High tensile textile plies.

Cover:

Black, smooth rubber, weather and abrasion resistant. Fabric impression.

Working Pressure:

1233 PSI, 85 bar

Nominal Burst Pressure:

2466 PSI, 170 bar

Temperature:

-40°F/+158°F (-40°C /+70°C)

Marking:

 PARAGON



 PART NO.	 Inner Diameter		 Outside Diameter		 Weight		 Max. L	No Wire
	Inch	mm	Inch	mm	Lbs./Ft	Kg/m	ft/m	
GRH-100-1233	1	25.4	1.69	43	0.7	1.04	61/200	4
GRH-125-1233	1 1/4	31.8	1.87	48	0.9	1.34	61/200	4
GRH-150-1233	1 1/2	38.1	2.32	59	1.1	1.64	61/200	4
GRH-200-1233	2	51	2.83	72	1.4	2.08	61/200	4
GRH-250-1233	2 1/2	63	3.43	87	2.0	2.98	61/200	6
GRH-300-1233	3	76	3.97	101	2.7	4.02	61/200	6
GRH-400-1233	4	102	5.12	130	3.8	5.65	61/200	6