Firewater Deluge Hose

Application:
Delivery hose for firewater deluge service on oil rigs. ABS approved; fire tested to EN 15540:1999 (800 °C for 30 minutes).

Tube:
Black, smooth CR rubber

Reinforcement:
High strength steel cord

Cover:
Glass fiber layers co-vulcanized with an external layer of red CR rubber; fire, sea water, abrasion and ozone resistant

Size range:
2" – 6" (51 mm – 152 mm)

Working pressure:
300 PSI

Temperature:
-40°F/+212°F (-40°C/+100°C)

Best for:
Firewater deluge service on oil rigs

Marking:



ID		OD		WORKING PRESSURE		BURST PRESSURE		BEND RADIUS		WEIGHT		COIL LENGTH	
in	mm	in	mm	PSI	bar	PSI	bar	in	mm	lb/ft	kg/m	ft	m
2"	51	3.16	80	300	21	1500	103	16.54	420	3.29	4.9	196.8	60
3"	76	4.23	107	300	21	1500	103	21.06	535	5.04	7.5	196.8	60
4"	102	5.28	134	300	21	1500	103	25.2	640	7.39	11	196.8	60
5"	127	6.3	160	300	21	1500	103	43.31	1100	9	13.39	196.8	60
6"	152	7.28	185	300	21	1500	103	47.64	1210	10.55	15.7	196.8	60