



## VACUUM ABRASION HOSE

Premium EPDM 300 suction hose

### Application:

Heavy duty EPDM liquid suction hose for industrial and agricultural water, Cesspool cleaning, Slurry and sludge handling, light chemical, dry material and marine use.

### Temperature:

-40°F/+176°F (-40°C /+80°C)

### Tube:

Black smooth EPDM rubber.

### Marking:

 PARAGON



### Reinforcement:

High polymerization helix.

### Cover:

Green corrugated helix.



 PART NO.	 ID		 OD		 w. p.	 Vacc.	 Min. b. r.	 Weight		 Max. L
	Inch	mm	Inch	mm	Psi	In. hg	Inch	Lb/FT	Kg/m	ft/m
PE300-100-LL	1	25.4	1.38	35	60	29.8	2	0.23	0.34	100/30
PE300-125-LL	1 ¼	31.8	1.62	41.1	60	29.8	3.3	0.34	0.50	100/30
PE300-150-LL	1½	38.1	1.93	49	60	29.8	3.3	0.40	0.59	100/30
PE300-200-LL	2	51	2.5	63.5	60	29.8	5.2	0.66	0.98	100/30
PE300-250-LL	2½	63	3.1	78.7	50	29.8	5.5	0.93	1.38	100/30
PE300-300-LL	3	76	3.55	90.1	44	29.8	7.1	1.11	1.65	100/30
PE300-400-LL	4	102	4.6	116.8	38	29.8	11.0	1.85	2.75	100/30
PE300-500-LL	5	127	5.75	146	28	28.0	16.5	2.15	3.19	100/30
PE300-600-LL	6	152	6.8	172.7	23	28.0	20	3.07	4.56	100/30